

GTS NX

Heavy rainfall during deep excavation
nearby a river channel

MIDAS Taiwan

Note: The parameters in the example use assumed conditions.



Water Pressure

GTS NX can consider water pressure that occurs from the defined water level of a model. Water pressure is added as an edge pressure load for 2D problems and as a surface pressure load for 3D problems.

The pressure size needed for calculating the water pressure is determined as follows:

1. Same size as the pore pressure defined on the target edge/surface ($Z_{\text{coordinate}}$)
2. Hydrostatic pressure due to user input water level position , ($Z_{\text{water Level}}$)

$$P = \rho \times g \times (Z_{\text{water Level}} - Z_{\text{coordinate}}) = 196.2(\text{KPa}) = 196.2(\text{KN/m}^2)$$




Reference


GTS NX_Analysis Reference_Chapter6_LoadConstraint

Explanation-1


Stage 1




Stage 2




Stage 3



Stage 4






Water Pressure



Explanation-2

Before stage 3 of excavation





Heavy rainfall 72 hours attack






Part1. Geometry

MIDAS Taiwan


Import




Import






Surface merging






Selecting all




Do not tick




Import excavation area



Imprint



Target Object: All surfaces




Tool Object: Excavation zone


Shortest path line selected




Delete curves



Step1.Excavation curves



Step2. DELETE




Part2. Soil Property

MIDAS Taiwan




Soil Layer Distribution

Water Pressure



Note: The parameters in the example use assumed conditions.

Property Import





Excavation area – Stage 1 -1




Mesh size: 1/ Prop: Silty layer


Geometry set: Excav 1_Soil1



Mesh set: Excav1_Soil1



Geometric features are automatically hidden during mesh generation




- Mesh
 - Default Mesh Set
 - 開挖1_soil1
 - 開挖2_soil1
 - 開挖3_soil1


Excavation area –Stage 2 -2

Mesh size: 1/ Prop: Silty sand layer

Soil 1
Geometry set: Excav2 




Soil 1
Mesh set: Excav2 



Geometry set: Excav3  Soil 1



Mesh set: Excav3  Soil 1



- Mesh
 - Default Mesh Set
 - 開挖1_soil1
 - 開挖2_soil1
 - 開挖3_soil1
 - 開挖3_soil2
 - 最終開挖_soil2

Excav area – Stage 3 -3

Mesh size: 1/ Prop: Weathered soil

Geometry set: Excav3_Soil2




Mesh set: Excav3_Soil2



Geometry set: Excav4_Soil2



Mesh set: Excav 4_Soil2




Riverbank area

Separated mesh set


Embankment-mesh size: 1

Gravel-mesh size:1

Existing dike-mesh size:1



Soil Layer




Part3. Mesh

MIDAS Taiwan

Retaining Wall-1D Beam



Extracting 1D element to retaining wall




Tick on to view the property shape of BEAM



Raft foundation-1D Beam



Extracting 1D element to raft foundation



Tick on to view the property shape of BEAM




Center Column-1D Beam



Center column(depth 24m)
(H350 ×250 ×12 ×19)-Beam

Extracting 1D element to center column



Tick on to view the property shape of BEAM




Strut Layer1-1D Truss



Strut Layer1-H Beam-Steel
(H300 ×300 ×13 ×21)-Truss


Extracting 1D element to strut_Layer1




Tick on to view the property shape of STRUSS



Strut Layer2&3-1D Truss




Element Local Orientation





Part4.Boundary Conditions

MIDAS Taiwan



Boundary Conditions



BC for 2-sided edges





Constraint Ry for center column




Initial Water Head Level


(Nodal Head ,Pressure=0 m)




Edge features selected




Initial Seepage Surface




Selecting line features




Excav Stage1_Seepage Surface




Excav Stage2_Seepage Surface



Selecting line features





Excav Stage 3_Seepage Surface





Selecting line features

Excav Stage4_Seepage surface




Water Pressure

(Pressure to represent for river reservoir pressure)



Water level (10m)

Selecting line features



Part5.Interface Elements

MIDAS Taiwan

Interface Element-1

GTS NX Interface Element Wizard

- Automatic calculation of normal stiffness (Kn) & tangential stiffness (Kt)
- **Virtual Thickness Factor (tv)**
 - Range from 0.01 ~ 0.1 °
 - Use smaller values for higher stiffness °
- **Strength Reduction Factor (R)**
 - Sandy soil/Steel material = R : 0.6~0.7
 - Clay/Steel material = R : 0.5
 - Sandy soil/Concrete = R : 1.0~0.8
 - Clay/Concrete = R : 1.0~0.7

Manual definition

Interface Nonlinearities: **None**

Structural Parameters

Normal Stiffness Modulus(Kn): **0 kN/m³**

Shear Stiffness Modulus(Kt): **0 kN/m³**

Automatic by Wizard

Interface Wizard Data

Structural Parameters

Strength Reduction Factor(R): **1**

Virtual Thickness Factor(tv): **0.1 m**




Consider Element Size

Line Interface Thickness: **1 m**

Conduction for Seepage flow: **0 m/sec/m**

OK **Cancel**

Interface Element-2



Creating Rigid link for soil and retaining wall before RW is constructed

Interface Element-3

Normal stiffness (Kn) & Tangential stiffness (Kt)


- 水平支撐1-H型鋼-Steel
- 水平支撐2-H型鋼-Steel
- 水平支撐3-H型鋼-Steel
- Line Interface
- Rigid Link Mesh

- Rigid Link (Rigid Link)
- Interface Property(Wizard)..

Line Interface



Rigid Link



Part6. Construction Stage

MIDAS Taiwan

Construction Stage-1

(Selecting type of simulation)




GTS NX Type of simulation

Stress
Seepage
Stress-Seepage-Slope
Consolidation


Stress Seepage Slope

Seepage-Thermal Stress
Heat of Hydration(Thermal Stress)
Fully Coupled Stress Seepage Heat
Stress-Seepage-Slope-Nonlinear Time History




Step1.New

Step2.Define CS



CS definition window

Displaying all mesh sets/ BCs/ Geometry sets



Construction Stage-2

Stage0. Initial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m


Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-3

Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-4

Stage0. Initial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-5

Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-6

Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m


Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-7

Stage0. Initial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-8

Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2 -5m


Stage5.Strut2 -4m

Stage6.Ex3 -9m

Stage7.Strut3 -8

Stage8.Fx4 -12m

Stage9.Raft foundation (t= 1m)



Construction Stage-9

Stage0. Initial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m


Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-10

Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)



Construction Stage-11

Stage0. Initial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m



Stage5.Strut2_-4m

Stage6.Ex3_-9m

Stage7.Strut3_-8m

Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)




Part7. Analysis & Calculation

MIDAS Taiwan

Analysis


(Deep excavation nearby river channel)




Analysis type: Construction Stage

Construction Stage

- Linear Static
- Nonlinear Static
- Construction Stage**
- Eigenvalue
- Response Spectrum
- Linear Time History(Modal)
- Linear Time History(Direct)
- Nonlinear Time History
- Nonlinear Time History + SRM
- 2D Equivalent Linear
- Consolidation
- Fully Coupled Stress Seepage
- Seepage(Steady-state)
- Seepage(Transient)
- Slope Stability(SRM)
- Slope Stability(SAM)



Calculation




Results-1

Sequence of analysis in CS


- 河道周邊深開挖
 - + Stage0.未施工前-Seepage
 - + Stage0.未施工前-Stress
 - + Stage1.連續壁(24m)和中間柱施-Seepage
 - + Stage1.連續壁(24m)和中間柱施-Stress
 - + Stage2.開挖1(開挖深度-2m)-Seepage
 - + Stage2.開挖1(開挖深度-2m)-Stress
 - + Stage3.水平支撐1(位置-1m)-Seepage
 - + Stage3.水平支撐1(位置-1m)-Stress
 - + Stage4.開挖2(開挖深度-5m)-Seepage
 - + Stage4.開挖2(開挖深度-5m)-Stress
 - + Stage5.水平支撐2(位置-4m)-Seepage
 - + Stage5.水平支撐2(位置-4m)-Stress
 - + Stage6.開挖3(開挖深度-9m)-Seepage
 - + Stage6.開挖3(開挖深度-9m)-Stress
 - + Stage7.水平支撐3(位置-8m)-Seepage
 - + Stage7.水平支撐3(位置-8m)-Stress
 - + Stage8.最終開挖 (-12m)-Seepage
 - + Stage8.最終開挖 (-12m)-Stress
 - + Stage9.筏基梁版(t=1m)-Seepage
 - + Stage9.筏基梁版(t=1m)-Stress



施工階段0_Flow Path




施工階段9_Flow Path



Results-2

(Total Translation(m))

Stage2



Stage0.Intial condition

Stage1.RW (24m) & center column

Stage2.Ex1_-2m

Stage3.Strut1_-1m

Stage4.Ex2_-5m

Stage5.Strut2_-4m


Stage6.Ex3_-9m

Stage7.Strut3_-8m


Stage8.Ex4_-12m

Stage9.Raft foundation (t= 1m)


Stage4



Stage6



Stage6






Part8. Heavy rainfall assessment

MIDAS Taiwan

Before Excav Stage 3

Heavy rainfall struck 72 hours continuously



Rainfall Recording

(Hours)

Unit (kn/m/J/hr)

kN m J hr




Seepage Boundary



時間累計(hr)	每6小時降雨量 (m)
0	0
6	0.04
12	0.1
18	0.18
24	0.2
30	0.18
36	0.15
42	0.12
48	0.1
54	0.08
60	0.06
66	0.04
72	0.03

Copy & paste recording data



開啟Excel



註:GTS NX不支援Y軸單位切換。

Surface Flux


Unit (KN/m/J/hr)

kN m J hr

Seepage/Consolidation Analysis



Selecting line features



Flux=Value x Function



Note:

if surface flux > coefficient of permeability
total head = potential head

(meaning of the velocity is ignore due to the higher of pressure & elevation of flux)

Heavy Rainfall Assessment-1

New CS type: Stress-Seepage-slope

Construction Stage Set

Name	強降雨危害評估	Add
Stage Type	Stress-Seepage-Slope	Modify
No	Name	Type
2	Construction Stage Set-1	Stress-Seep...
3	強降雨危害評估	Stress-Seep...

Copy
Delete
Define CS...
Close

Step1. Select stage6

Construction Stage Set Name: 強降雨危害評估

Stage ID	8: Stage6.開挖3(開挖深度-9m)-1	Move to Previous	Move to Next
Stage Name	Stage6.開挖3(開挖深度-9m)-1	New	Insert
Stage Type	Stress Seepage	Delete	

Step2. Insert

Step3. Select the previous construction stage

Heavy Rainfall Assessment-2

7: 強降雨危害評估

強降雨危害評估

Stress Transient Seepage

Define Construction Stage

Construction Stage Set Name: 強降雨危害評估

Stage ID: 7: 強降雨危害評估

Stage Name: 強降雨危害評估

Stage Type: Stress Transient Seepage

Activated Data

Continuous rainfall condition

Time Step

Duration: 72 hr

User Defined Step

Step Number: 24


Save Result:

Log Scale:

Generate Step

	Time	Load Factor	Save Step
▶	3.0000	0.0417	<input checked="" type="checkbox"/>
	6.0000	0.0417	<input checked="" type="checkbox"/>
	9.0000	0.0417	<input checked="" type="checkbox"/>
	12.0000	0.0417	<input checked="" type="checkbox"/>
	15.0000	0.0417	<input checked="" type="checkbox"/>
	18.0000	0.0417	<input checked="" type="checkbox"/>
	21.0000	0.0417	<input checked="" type="checkbox"/>
	24.0000	0.0417	<input checked="" type="checkbox"/>


Analysis-1




Construction Stage

- Linear Static
- Nonlinear Static
- Construction Stage**
- Eigenvalue
- Response Spectrum
- Linear Time History(Modal)
- Linear Time History(Direct)
- Nonlinear Time History
- Nonlinear Time History + SRM
- 2D Equivalent Linear
- Consolidation
- Fully Coupled Stress Seepage
- Seepage(Steady-state)
- Seepage(Transient)
- Slope Stability(SRM)
- Slope Stability(SAM)

Analysis type: Construction Stage



Analysis-2



Tick on

Automatically Consider Water Pressure


Tick on

Estimate initial stress of activated elements

Tick on


Estimate initial Configuration of activated nodes

Calculation




Results

Sequence of analysis in CS



Heavy rainfall consideration



Stage6.Ex3_-9m

No rainfall consideration

